


Tapered roller bearing 30315-DR-JTEKT - 31315-KOYO

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/31315-koyo>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
75	160	40	37	28	222	266	2 100	2 900	30315DR					
Dimension series to ISO355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	48.8	89	91	148	127	151	6	14	2.5	2	0.81	0.74	0.41	3.48

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122149
Inside diameter	75 mm
Inside diameter	2.953" inch
Outside diameter	160 mm
Outside diameter	6.299" inch
Thickness	40 mm
Thickness	1.575" inch
Weight	3516 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE